

## DIGITAL PRESSURE GAUGE 1.5"

### NF.DPG3600

**Pressure Range: 0 to 150 psi**  
**Temperature Compensation: -10 to +60°C**  
**Unit Selection: Psi, Bar, Mpa, Kg/cm<sup>2</sup> available**  
**Auto-Off Function**  
**Longer Battery Life**

DPG3600 Digital Pressure Gauge is designed to handle applications which require air pressure measurement under normal or indoor environment. The user-friendly DPG3600 having longer battery life of 1 year typical at sampling rate of 1.2 sec. With a sensor, a display compactly integrated inside with variety of functions such as unit selection, and auto-off as an option etc, and this gauge can be used for a variety of industrial and commercial applications.






#### TECHNICAL DATA

**Type:** DPG3600-B: LCD Display + Battery Power  
**Socket Material:** Brass  
**Power Supply:** Battery CR2450 (3.0V, 500mAh)  
**Sampling Rate:** 1.2 sec  
**Battery Life:** 1 Year for continuous use  
**Pressure Range:** 0~150 PSI  
**Measure Media:** Dry Air  
**Burst Pressure:** 2 x F.S.  
**Accuracy:** ±1% F.S. (@25±3°C)  
**Unit:** Psi, Bar, Mpa, Kg/cm<sup>2</sup> available  
**Resolution:** 0.1Psi, 0.01Bar, 0.001Mpa, 0.01Kg/cm<sup>2</sup>  
**Compensated Temperature Range:** -10 ~ +60°C  
**Humidity:** 35~85% RH  
**Brass Port:** 1/8"NPT, 1/4"NPT or PT Male, option available  
**Weight:** approx. 0.1 kg

#### Approvals:



#### DIMENSIONS



#### Dimensions Data

Connection Size	A
1/4"NPT Male	12 mm
1/8"NPT Male	10 mm

unit=mm

Le caratteristiche dichiarate possono cambiare senza alcun preavviso



Per ordini:  
 Tel.: +39 011 198 218 39  
 E-mail: commerciale@asit-ge.com



# DIGITAL PRESSURE GAUGE 1.5"

## NF.DPG3600

### ORDERING INFORMATION

DPG3600	Code	Type										
	<b>B</b>	LCD Display + Battery Power										
		<table border="1"> <thead> <tr> <th>Code</th> <th>Pressure Range</th> </tr> </thead> <tbody> <tr> <td><b>1</b></td> <td>150 psi</td> </tr> <tr> <td><b>2</b></td> <td>Others</td> </tr> </tbody> </table>	Code	Pressure Range	<b>1</b>	150 psi	<b>2</b>	Others				
Code	Pressure Range											
<b>1</b>	150 psi											
<b>2</b>	Others											
		<table border="1"> <thead> <tr> <th>Code</th> <th>Connection Port</th> </tr> </thead> <tbody> <tr> <td><b>A</b></td> <td>1/8"NPT male</td> </tr> <tr> <td><b>B</b></td> <td>1/4"NPT male</td> </tr> <tr> <td><b>C</b></td> <td>1/4"PT male</td> </tr> <tr> <td><b>O</b></td> <td>Option</td> </tr> </tbody> </table>	Code	Connection Port	<b>A</b>	1/8"NPT male	<b>B</b>	1/4"NPT male	<b>C</b>	1/4"PT male	<b>O</b>	Option
Code	Connection Port											
<b>A</b>	1/8"NPT male											
<b>B</b>	1/4"NPT male											
<b>C</b>	1/4"PT male											
<b>O</b>	Option											
		<table border="1"> <thead> <tr> <th>Code</th> <th>Power Supply</th> </tr> </thead> <tbody> <tr> <td><b>A</b></td> <td>Battery CR2450 (3.0V, 500mAh)</td> </tr> </tbody> </table>	Code	Power Supply	<b>A</b>	Battery CR2450 (3.0V, 500mAh)						
Code	Power Supply											
<b>A</b>	Battery CR2450 (3.0V, 500mAh)											
<b>DPG3600</b>		<b>Complete Ordering Code</b>										

Le caratteristiche dichiarate possono cambiare senza alcun preavviso



Per ordini:  
Tel.: +39 011 198 218 39  
E-mail: commerciale@asit-ge.com



## ASIT ITALIA S.r.l.

### Sede operativa e Uffici

Via Quintino Sella, 6 - 10020 Riva presso Chieri (TO)

T +39 011 198 218 39 - F +39 011 198 371 06

<http://www.asit-ge.com> - [info@asit-ge.com](mailto:info@asit-ge.com)

