


HYDROSTATIC LEVEL TRANSMITTER

AI.Hydro.00



INTRODUCTION

AI.Hydro.00 is made from high-quality silicon piezoresistive sensor.

The piezoresistive sensor is packaged in stainless steel housing.

AI.Hydro.00 is precision engineered to fit most level measurement.

The water-proof cable connects with housing sealed, with vented tube putting in, the transmitter could be used in the water or liquid in a long time. Integrated construction and standard output signal could provide easy operation and good automatic control.

FEATURES

- Measuring ranges from 1mH₂O to 200mH₂O
- Accuracy: +/-0-25%FSO or +/-0.5%FSO
- Calibrated and temperature compensated
- Stainless steel construction
- Cable material: PUR
- Piezoresistive pressure sensor design
- Variety of Pressure & Electrical connections
- Output 4..20mA, 0..10V, 0..5V, RS485 and others
- Connection via HART Protocol and programmable via Modem + Smartphone App

APPLICATIONS

- Level measurement
- Hydraulic monitoring in rivers and sea
- Muddy liquid level measurement
- Water treatment
- Water diversion project

TECHNICAL SPECIFICATIONS STANDARD PRESSURE RANGES

Nominal pressure	gauge	
0...1mH ₂ O	●	
0...2mH ₂ O	●	
0...5mH ₂ O	●	
0...10mH ₂ O	●	
0...15mH ₂ O	●	
0...20mH ₂ O	●	
0...50mH ₂ O	●	
0...80mH ₂ O	●	
0...100mH ₂ O	●	
0...150mH ₂ O	●	
0...200mH ₂ O	●	

PERFORMANCE SPECIFICATIONS

Parameter	Value	Units	Notes
-----------	-------	-------	-------

General

Pressure Range	0-1, ..., 200	mH ₂ O	
Overpressure	1.5xFS	mH ₂ O	

Environmental

Operating Temperature Range	-20 to +70	°C	-4°F to 158°F
Compensated Temperature Range	0 to +60	°C	32°F to 158°F
Storage Temperature Range	-40 to +125	°C	-40°F to 257°F
Vibration	10	g	20 to 2000Hz
Shock	100	g	10ms
Cycles	10x10 ⁶	cycles	

Electrical @25°C(77°F)

Output Signal	4...20mA	0...5Vdc	0...10Vdc	RS485	4...20mA+HART
Power Supply(Vs)	12...36Vdc	12...36Vdc	15...36Vdc	12...36Vdc	5Vdc
Load Resistance	<(Vs-12)/0.02A (For current output), >10kΩ (For voltage output)				
Insulation Resistance	100MΩ@50Vdc				

Physical Specifications

Media Compatibility	All media compatible with 316L stainless steel				
Housing	304 stainless steel				
Diaphragm	316L stainless steel				
Seal Ring	Viton or NBR				
Oil Filling	Silicone oil				
Protection	IP68				
Net Weight	Approx.225g				

Parameter	Minimum	Typical	Maximum	Units	Notes
-----------	---------	---------	---------	-------	-------

Performance


Accuracy	0.1	0.25	0.5	%FSO	1,2
Temp Coeff - Zero		±0.75	±1.5	%FSO	3
Temp Coeff - Span		±0.75	±1.5	%FSO	3
Long-Term Stability		±0.2	±0.3	%FSO/year	1

Notes

1. All values measured at 25°C (77°F)
2. Including non-linearity, hysteresis and repeatability.
3. 0°C to 70°C (32°F to 158°F) with reference to 25°C (77°F).

The listed specifications and dimensions are subject to change without prior notice.



DIMENSIONS





BC - CONNECTION BOX

- IP65 protection
- Material: PBT plastic highly resistant to external humidity and accidental impacts
- Possibility of wall or Omega bar mounting
- Complete with terminal block for connection to the AI.Hydro.00 level transmitter
- Including cable glands


TYPE 1



TYPE 2



ELECTRICAL CONNECTION



Cable outlet



	2-wire(current)	3-wire(voltage)	4-wire(RS485)
Supply+	red	red	red
Signal+	yellow	yellow	yellow
Gnd	-	black	-
RS485A	-	-	green
RS485B	-	-	white

ORDER CODE

AI.Hydro.00	Hydrostatic Level Transmitter		
	Range mH2O		
	0-1/ 0-2/ 0-5/ 0-10/ 0-20/ 0-50/ 0-80/ 0-100/ 0-150/ 0-200		
	Cable Length (PUR Material)		
	1: Standard 5m/ 2: Xm		
	Output		
	mA: 4-20 mADC+HART/R4: RS485/R40: RS485+4..20mA/V: 0-10V DC/J: 0-5V DC/F: 1-5V DC/		
	Material		
	Diaphragm	Pressure Port	Housing
SS	SS316L	SS304	SS304
	Process connection		
	F1: flanged connection 1" ANSI 150rf	F1: DN25/PN16 (specify PN)	
	F2: flanged connection 2" ANSI 150rf	F3: DN50/PN16 (specify PN)	
	F4: flanged connection 3" ANSI 150rf	F5: DN80/PN16 (specify PN)	
	F6: flanged connection 4" ANSI 150rf	F7: DN100/PN16 (specify PN)	
	G0: without cable gland		
	PG: PG13,5 PA threaded cable gland with lock nut		
	G: 1" GAS male cable gland in AISI 316 threaded connection adjustable load-bearing cable top case mounting		
	G1: 1 1/2" GAS male cable gland in AISI 316 threaded connection adjustable load-bearing cable mounting box top		
	G2: 2" GAS male cable gland in AISI 316 threaded connection adjustable load-bearing cable mounting box top		
	O: options to be agreed		
	BC - BOX CONNECTION		
	1: type 1		
	2: type 2		
	0: no		

Example order code:

	<i>Range</i>	<i>Cable length</i>	<i>Output</i>	<i>Material</i>	<i>Process Connection</i>	<i>Box Connection</i>
AI.Hydro.00	0-1mH2O	1: standard 5m	mA	SS	F3	G

Description Code:

Hydrostatic Level Transmitter Model AI.Hydro.00

0-1mH2O: Range

1: Cable length standard 5m

mA: Output 4-20mADC+HART, 2 wire

SS: Material Diaphragm SS316L, Pressure Port SS304 e Housing SS304

F3: Flanged connection DN50 / PN16 with 1 "GAS female threaded central hole, for mounting threaded connection cable

G: threaded connection adjustable cable 1"

1: Box Connection Type 1



ASIT ITALIA S.R.L.

Sede operativa e Uffici

Via Quintino Sella, 6

10020 Riva presso Chieri (TO)

T (+39) 011 198 218 39 - F (+39) 011 198 371 06

INFO@ASIT-GE.COM

WWW.ASIT-GE.COM



Member of CISQ Federation



CERTIFIED MANAGEMENT SYSTEM
ISO 9001

Company with
Certificate of Quality
System ISO 9001:2015
Cert n°38785/19/S