

## SINGLE STRAIGHT-TUBE MODEL

### OC.STMASSMKII



#### GENERAL

Easy-to-clean single, straight tube Coriolis flowmeter capable of accurate flowmetering for a broad range of applications.

#### FEATURES

- High accuracy
- Easy-to-clean construction
- Both temperature and density measurable.

#### MAJOR SPECIFICATIONS

Nominal size	15, 25, 40, 50, 80mm
Connection	JIS 10, 20K Flange
	ASME/JPI 150 Flange
Applicable fluids	Liquid
Flow range	0 to 108000kg/h (6 types)
Operating temp. range	-25 to +130°C (non-explosionproof)
Max. operating pressure	2.45MPa (Depends on connection standard)
Accuracy	±0.2% of RD±ZS *
Power supply	AC or DC-powered
Major part material	SUS316L
Configuration	Explosionproof or non-explosionproof
Output	Flowrate, temperature, density (liquid), status

\*: ZS=Zero point stability error

Le caratteristiche dichiarate possono cambiare senza alcun preavviso



Per ordini:  
Tel.: +39 011 198 218 39  
E-mail: commerciale@asit-ge.com



## ASIT ITALIA S.r.l.

### Sede operativa e Uffici

Via Quintino Sella, 6 - 10020 Riva presso Chieri (TO)

T +39 011 198 218 39 - F +39 011 198 371 06

<http://www.asit-ge.com> - [info@asit-ge.com](mailto:info@asit-ge.com)

